

620 Series Brass Gate Valve IPS, Full Port

SPECIFICATIONS

TEMPERATURE RATING: 180°FSTEAM RATING MAX.: 320°F


• PRESSURE RATING: 200 WOG | NON-SHOCK

FULL PORTANSI B1.20.1

COMPONENTS						
NO.	BODY PART	MATERIAL				
1	NUT	HOT ROLLED SAE 1010R				
2	NAME PLATE	ALUMINUM A1100				
3	HANDLE	CAST IRON JIS ZZ2202				
4	PACKING NUT	BRASS ROD C37700				
5	GLAND RING	BRASS ROD C37700				
6	PACKING	NBR SN-719F				
7	BONNET	CAST BRASS C85700				
8	PACKING	FIBER				
9	STEM	BRASS ROD C37700 CAST BRASS C85700				
10	LOCK NUT	BRASS ROD C37700				
11	DISC	CAST BRASS C85700				
12	BODY	CAST BRASS C85700				

DIMENSION	IS				(INCHES)
SIZE	d	D	Н	L	FLOW RATE (GPM)
1/4"	0.43	2.09	2.91	1.71	8.85
3/8"	0.47	2.09	2.91	1.71	16.48
1/2"	0.53	2.09	2.91	1.71	21.81
3/4"	0.75	2.13	3.31	1.81	42.15
1"	0.98	2.48	3.90	2.13	71.18
1 1/4"	1.26	2.72	4.61	2.24	109.25
1 1/2"	1.50	3.15	5.08	2.44	167.00
2"	1.93	3.52	5.98	2.70	193.38
2 1/2"	2.44	3.98	7.87	3.70	337.55
3"	2.95	4.37	8.82	4.02	502.68
4"	3.62	4.84	9.88	4.53	548.87





All information contained herein is supplied by manufacturer and deemed to be accurate. Information is subject to change without notice. Purchaser is responsible for proper installation, use and maintenance of product. Southern Valve & Fitting USA, Inc. passes on manufacturer's warranty but extends no other warranty. All products sold by Southern Valve & Fitting USA, Inc. are subject to its full terms and conditions of sales as published and available on request. Any warranty made extends to original purchaser and is not assignable or transferable.