




609-9241L Series Bugatti Forged Brass Ball Valve FIP×FIP, Large Steel Handle









- ASSEMBLY IN RIGID PIPE SYSTEM
- KV: FLOW COEFFICIENT M³/H
- DIRECTION OF FLOW: BOTH DIRECTIONS
- TEMPERATURE RANGE: -20°C / +120°C
- MAXIMUM PRESSURE:

600 WOG (WATER, OIL, GAS) 70 PSI LP GAS

OPSILP GAS

150 WSP (WORKING STEAM PRESSURE)

UL/FM/CSA

COMPONENTS						
NO.	PART NAME	MATERIAL				
1	BODY	CW510L				
2	END CONNECTION	CW510L				
3	BALL SEAL	PTFE				
4	BALL	CW510L				
5	STEM	CW614N				
6	LOWER SEAL	PTFE				
7	O-RING	NBR70SH				
8	UPPER SEAL	PTFE				
9	BRASS RING	CW614N				
10	NUT	STEEL				
11	HANDLE	STEEL				

DIMENSI	(INCHES)				
SIZE	Α	В	С	D	СН
1/2"	2.09	1.57	3.35	0.46	0.98
3/4"	2.28	1.77	3.80	0.49	1.22
1"	2.80	2.03	3.80	0.59	1.50
1 1/4"	3.23	2.32	4.72	0.62	1.85
1 1/2"	3.70	2.60	4.72	0.64	2.13
2"	4.13	3.27	6.38	0.65	2.64
2 1/2"	5.80	4.98	7.48	1.06	3.22
3"	6.71	5.59	8.86	1.14	3.78
4"	7.70	6.18	8.86	1.22	4.80

All information contained herein is supplied by manufacturer and deemed to be accurate. Information is subject to change without notice. Purchaser is responsible for proper installation, use and maintenance of product. Southern Valve & Fitting USA, Inc. passes on manufacturer's warrantee but extends no other warrantee. All products sold by Southern Valve & Fitting USA, Inc. are subject to its full terms and conditions of sales as published and available on request. Any warrantee made extends to original purchaser and is not assignable or transferable.