

## 9681 Series Bugatti One Piece Body Ball Valve F/F with Lever Handle





- ASSEMBLY IN RIGID PIPE SYSTEM
- NOMINAL PRESSURE (PN) IN BAR: 200 PSI
- DIRECTION OF FLOW: BOTH DIRECTIONS
- TEMPERATURE RANGE: -4°F TO 140°F
- USE: GAS


SPECIFICATION	
THREAD ENDS	FEMALE/FEMALE ANSI B1.20.1
ORIFICE	0.35 TO 0.59
ACTUATOR	ALUMINUM LEVER HANDLE
OPERATOR	90° ROTATION WITH MECHANICAL STOP

DIMENSIONS						(INCHES)
SIZE	DN	Α	В	С	D	СН
3/8"	0.35	2.07	1.46	2.28	0.41	0.87
1/2"	0.43	2.32	1.46	2.28	0.54	0.98
3/4"	0.59	2.60	1.61	2.28	0.56	1.22

COMPONENTS						
NO.	PART NAME	MATERIAL	QTY			
1	BODY	CW617N	1			
2	BALL SEAL	PTFE	2			
3	BALL	CW617N, NI+CR PLATED	1			
4	COMPRESSION RING	CW614N	1			
5	O-RING	NBR70SH	1			
6	STEM	CW614N	1			
7	O-RING	NBR70SH	2			
8	HANDLE	ALUMINUM	1			
9	SCREW	STEEL, ZINC PLATED	1			







All information contained herein is supplied by manufacturer and deemed to be accurate. Information is subject to change without notice. Purchaser is responsible for proper installation, use and maintenance of product. Southern Valve & Fitting USA, Inc. passes on manufacturer's warranty but extends no other warranty. All products sold by Southern Valve & Fitting USA, Inc. are subject to its full terms and conditions of sales as published and available on request. Any warranty made extends to original purchaser and is not assignable or transferable.